

slim
profile



18 mm



**Open voice video door entry kit
with 7" monitor.**

KITS



K40900

Video door entry kit with 7" open voice monitor and metal entrance panel

Contents:

- 1 7" open voice colour monitor.
- 1 metal entrance panel.
- Surface mounting accessories.
- 1 power supply, 100-240 Vac 0.5 A 50-60 Hz / 17 V 900 mA with 2P 10 A europlug.



K40902

Video door entry kit with 7" open voice monitor and metal entrance panel

Contents:

- 1 7" open voice colour monitor.
- 1 metal entrance panel.
- Surface mounting accessories.
- 1 power supply, 100-240 Vac 0.5 A 50-60 Hz / 17 V 900 mA with British standard plug.



250 m max (*)



metal



night vision

MONITORS



K40901

Additional 7" monitor for KIT K40900

Contents:

- 1 7" open voice colour monitor.
- Surface mounting accessories.
- 1 power supply, 100-240 Vac 0.5 A 50-60 Hz / 17 V 900 mA with 2P 10 A europlug.



18 mm
slim profile

K40903

Additional 7" monitor for KIT K40902

Contents:

- 1 7" open voice colour monitor.
- Surface mounting accessories.
- 1 power supply, 100-240 Vac 0.5 A 50-60 Hz / 17 V 900 mA with British standard plug.



colour

Features:

- Connections with 2 wires (not polarised).
- * Guaranteed maximum distance of: 250 m with Elvox 732H or 732I cable; 100 m with 1 mm² or cat. 5/6 cable; 70 m with 0.5 mm² cable.
- 7" open voice colour monitor with capacitive keyboard, for call-answering, open electrical locks and camera self-activation.
- Extension with a second monitor.
- Flush or surface mounting.
- Die-cast metal entrance panel IP54 with rain cover and back-lit name card holder.
- Camera with white LED night-vision.
- Monitor size: 241x161x18 mm.
- Entrance panel size: 98x134x40 mm.

Example of kit wiring

